


BKBDR-RHP

Floor duct bend cover with anti-slip embossing




The floor duct bend cover BKBDR-RHP is placed on top of the BKB floor duct bend and protects cables and supply lines from flying sparks and other mechanical influences. It is 100 to 600 mm wide corresponding to the bend. The floor duct bend cover is made of sendzimir hot-dip galvanised steel with slip resistance class R12. With a maximum compartment size of 200 mm, we guarantee a tested load capacity of 5.00 kN according to EN 50085-2-2. They come with pre-assembled turning bolts.

DIN

Artikel	Typ	B	t	P _{max}	direction	W	W
BKBDR-RHP 10S	Floor duct bend cover	100 mm	2.00 mm	5.00 kN	horizontal	90°	0.360 kg
BKBDR-RHP 15S	Floor duct bend cover	150 mm	2.00 mm	5.00 kN	horizontal	90°	0.650 kg
BKBDR-RHP 20S	Floor duct bend cover	200 mm	2.00 mm	5.00 kN	horizontal	90°	0.940 kg
BKBDR-RHP 30S	Floor duct bend cover	300 mm	2.00 mm	5.00 kN	horizontal	90°	1.750 kg
BKBDR-RHP 40S	Floor duct bend cover	400 mm	2.00 mm	5.00 kN	horizontal	90°	2.840 kg
BKBDR-RHP 50S	Floor duct bend cover	500 mm	2.00 mm	5.00 kN	horizontal	90°	4.180 kg
BKBDR-RHP 60S	Floor duct bend cover	600 mm	2.00 mm	5.00 kN	horizontal	90°	5.780 kg

DETAIL- UND ANWENDUNGSBILDER





OPTIONALES ZUBEHÖR

DR-BK, BKDU 100, BKDU 110

DIN

Load requirements according to: EN 50085-2-2

