


BKBRDR-RHP

Floor duct bend cover with radius and anti-slip embossing




The BKBRDR-RHP floor duct bend cover is placed on top of the floor duct bend BKBR and protects cables and supply lines from flying sparks and other mechanical influences. It is 100 to 600 mm wide corresponding to the bend. The floor duct bend cover is made of sendzimir hot-dip galvanised steel with slip resistance class R12. With a maximum compartment size of 200 mm, we guarantee a tested load capacity of 5.00 kN according to EN 50085-2-2. They come with pre-assembled turning bolts.

DIN

Artikel	Typ	B	t	P _{max}	direction	W	W
BKBRDR-RHP 10S	Floor duct bend cover with curve	100 mm	2.00 mm	5.00 kN	horizontal	90°	0.990 kg
BKBRDR-RHP 15S	Floor duct bend cover with curve	150 mm	2.00 mm	5.00 kN	horizontal	90°	1.480 kg
BKBRDR-RHP 20S	Floor duct bend cover with curve	200 mm	2.00 mm	5.00 kN	horizontal	90°	2.050 kg
BKBRDR-RHP 30S	Floor duct bend cover with curve	300 mm	2.00 mm	5.00 kN	horizontal	90°	3.420 kg
BKBRDR-RHP 40S	Floor duct bend cover with curve	400 mm	2.00 mm	5.00 kN	horizontal	90°	5.110 kg
BKBRDR-RHP 50S	Floor duct bend cover with curve	500 mm	2.00 mm	5.00 kN	horizontal	90°	7.110 kg
BKBRDR-RHP 60S	Floor duct bend cover with curve	600 mm	2.00 mm	5.00 kN	horizontal	90°	9.430 kg

DETAIL- UND ANWENDUNGSBILDER



DR-BK, BKDU 100, BKDU 110

Load requirements according to: EN 50085-2-2