


## BKGRDR-RHP

Floor duct cover, right, with mitre cut and anti-slip embossing




The BKGRDR-RHP floor duct cover with a mitre cut on the right is placed on top of the BKGR floor duct branch and protects cables and supply lines from flying sparks and other mechanical effects. It is 100 to 600 mm wide corresponding to the branch. The floor duct cover is made of sendzimir hot-dip galvanised steel with slip resistance class R12. With a maximum compartment size of 200 mm, we guarantee a tested load capacity of 5.00 kN according to EN 50085-2-2. They come with pre-assembled turning bolts.

DIN

| Artikel        | Typ                                | B      | t       | P <sub>max</sub> | W        |
|----------------|------------------------------------|--------|---------|------------------|----------|
| BKGRDR-RHP 10S | Floor duct branch cover with mitre | 100 mm | 2.00 mm | 5.00 kN          | 0.630 kg |
| BKGRDR-RHP 15S | Floor duct branch cover with mitre | 150 mm | 2.00 mm | 5.00 kN          | 0.930 kg |
| BKGRDR-RHP 20S | Floor duct branch cover with mitre | 200 mm | 2.00 mm | 5.00 kN          | 1.260 kg |
| BKGRDR-RHP 30S | Floor duct branch cover with mitre | 300 mm | 2.00 mm | 5.00 kN          | 2.040 kg |
| BKGRDR-RHP 40S | Floor duct branch cover with mitre | 400 mm | 2.00 mm | 5.00 kN          | 2.990 kg |
| BKGRDR-RHP 50S | Floor duct branch cover with mitre | 500 mm | 2.00 mm | 5.00 kN          | 4.090 kg |
| BKGRDR-RHP 60S | Floor duct branch cover with mitre | 600 mm | 2.00 mm | 5.00 kN          | 5.350 kg |

## DETAIL- UND ANWENDUNGSBILDER





## OPTIONALES ZUBEHÖR

DR-BK, BKDU 100, BKDU 110

DIN

Load requirements according to: EN 50085-2-2

