



FERBOX® E02

Rebend connection, angled hooks perpendicular to the box

FERBOX® E02 single-row rebend connections are used for the frictional connection and reinforcement of reinforced concrete parts. They are suitable for narrow walls from 100 mm wall thick. They have the highest joint category – Interlocked – in transverse and longitudinal directions.. Their studded reinforcement box and cover are made of galvanised sheet metal and the reinforcing bars are made of B500 B or stainless steel. The bars have an L-shape parallel to the box for the first casting section. The FERBOX® box is either 800 or 1200 mm long and 60 to 135 mm wide. The standard diameter of the rods is 8 to 10 mm. Other versions and special solutions are available on request.



European Technical Assessment: ETA-20/0842

Article	G
512300022050 Ferb E02 85 08 100 1.20	3.480 kg
512300022051 Ferb E02 60 08 150 1.20	2.304 kg
512300022052 Ferb E02 60 08 200 1.20	2.016 kg
512300022053 Ferb E02 60 08 250 1.20	1.728 kg
512300022055 Ferb E02 60 10 150 1.20	3.552 kg
512300022057 Ferb E02 60 10 250 1.20	2.760 kg
512300022058 Ferb E02 85 12 100 1.20	7.776 kg
512300022059 Ferb E02 85 12 150 1.20	5.568 kg
512300022060 Ferb E02 85 12 200 1.20	4.128 kg
512300022061 Ferb E02 85 12 250 1.20	4.560 kg

G: Weight per storage unit



DETAIL AND APPLICATION IMAGES

