



FERBOX® EE

FERBOX® EE single-row connected rebend connections are used for the frictional connection and reinforcement of reinforced concrete parts. They are suitable for wide walls from 280 mm wall thick. They have the highest joint category – Interlocked – in transverse and longitudinal directions. Its studded reinforcement box and cover are made of galvanised sheet metal and the reinforcing bars are made of B500 B. The stirrups are U-shaped for the first casting section, ending in both parallel boxes. The FERBOX® box is either 800 or 1200 mm long and the stirrups are up to 500 mm wide. The standard diameter of the rods is 8 to 10 mm. Other versions and special solutions are available on request.



European Technical Assessment: ETA-20/0842

Article	G
512600022077 Ferb EE 60 08 150 1.20	5.808 kg
512600022078 Ferb EE 60 08 200 1.20	4.956 kg
512600022080 Ferb EE 60 10 200 1.20	6.876 kg
512600022082 Ferb EE 85 12 200 1.20	9.156 kg
512600022734 Ferb EE 60 08 150 0.8	3.872 kg
512600022735 Ferb EE 60 08 200 0.80	3.304 kg
512600022736 Ferb EE 60 10 150 0.80	5.584 kg
512600022737 Ferb EE 60 10 200 0.80	4.584 kg
512600022738 Ferb EE 85 12 150 0.80	7.968 kg
512600022739 Ferb EE 85 12 200 0.80	6.104 kg

G: Weight per storage unit



DETAIL AND APPLICATION IMAGES

