


GS

Threaded rod, DIN 976-1



GS threaded rods according to DIN 976-1 are available in galvanised and stainless steel (A4). They are available with M6, M8, M10, M12, M16 and M20 threads in lengths of 1000 mm and can be used for corresponding load capacities of 3.1 to 37.8 kN.

Artikel	Typ	B	L	W
GS10 GV	Threaded rods M10x1000	10 mm	1000 mm	0.489 kg
GS20 GV	Threaded rods M20x1000	20 mm	1000 mm	2.025 kg
GS16 GV	Threaded rods M16x1000	16 mm	1000 mm	1.327 kg
GS12 GV	Threaded rods M12x1000	12 mm	1000 mm	0.708 kg
GS6 GV	Threaded rods M6x1000	6 mm	1000 mm	0.169 kg
GS8 GV	Threaded rods M8x1000	8 mm	1000 mm	0.310 kg

Artikel	Typ	B	L	W
GS10 A4-70	Threaded rods M10x1000	10 mm	1000 mm	0.489 kg
GS20 A4-70	Threaded rods M20x1000	20 mm	1000 mm	2.025 kg
GS16 A4-70	Threaded rods M16x1000	16 mm	1000 mm	1.327 kg
GS12 A4-70	Threaded rods M12x1000	12 mm	1000 mm	0.708 kg
GS6 A4-70	Threaded rods M6x1000	6 mm	1000 mm	0.169 kg
GS8 A4-70	Threaded rods M8x1000	8 mm	1000 mm	0.310 kg

