



HED-P

Shear dowel

Half of the shear dowel HED-P is provided with a plasticised spring element, which makes a sliding sleeve unnecessary. The other half is made of stainless steel or galvanised steel. This combination makes it ideal for subsequent installation after the first construction phase. Drilling is used to insert the side with the plasticised spring element. The other side is cast during the second casting stage. The dowel shifts at right angles to the joint. Shear forces are transmitted vertically and parallel to the joint. The shear dowel HED-P is available in standard lengths of 300 to 500 mm for various diameters. Other lengths and diameters are available on request.

Artikel	Typ	L	D	W
550200003830	Schubdor HED P 20 500 V4A	500 mm	20 mm	1.300 kg
550200003831	Schubdor HED P 20 500 verz	500 mm	20 mm	1.300 kg
550200003832	Schubdor HED P 20 V4A	300 mm	20 mm	0.750 kg
550200003833	Schubdor HED P 20 verz	300 mm	20 mm	0.750 kg
550200003836	Schubdor HED P 22 500 V4A	500 mm	22 mm	1.550 kg
550200003837	Schubdor HED P 22 500 verz	500 mm	22 mm	1.550 kg
550200003838	Schubdor HED P 22 V4A	300 mm	22 mm	0.900 kg
550200003839	Schubdor HED P 22 verz	300 mm	22 mm	0.900 kg
550200003842	Schubdor HED P 25 500 V4A	500 mm	25 mm	2.200 kg
550200003843	Schubdor HED P 25 500 verz	500 mm	25 mm	2.200 kg
550200003844	Schubdor HED P 25 V4A	300 mm	25 mm	1.300 kg
550200003845	Schubdor HED P 25 verz	300 mm	25 mm	1.297 kg
550200003848	Schubdor HED P 30 500 V4A	500 mm	30 mm	2.850 kg
550200003849	Schubdor HED P 30 500 verz	500 mm	30 mm	2.850 kg
550200003850	Schubdor HED P 30 V4A	350 mm	30 mm	1.950 kg
550200003851	Schubdor HED P 30 verz	350 mm	30 mm	1.950 kg

OPTIONALES ZUBEHÖR

BRM

