



## HED-S

### Shear dowel

The shear dowel HED-S consists of a hot-dip galvanised or stainless steel dowel and a sleeve. When combined with the GS/GSQ stainless steel sliding sleeve or GK plastic sliding sleeve, the dowel can be shifted at right angles to the joint and transmits shear forces in a longitudinal and/or transverse direction. The shear dowel HED-S is available in standard lengths of 300 to 500 mm for various diameters. For example, it can absorb rated resistances for the load-bearing capacity of steel of up to 17.5 kN in joints up to 40 mm wide. Other lengths and diameters are available on request.

| Artikel      | Typ                        | L      | D     | W        |
|--------------|----------------------------|--------|-------|----------|
| 550100003854 | Schubdor HED S 20 500 V4A  | 500 mm | 20 mm | 1.250 kg |
| 550100003855 | Schubdor HED S 20 500 verz | 500 mm | 20 mm | 1.250 kg |
| 550100003856 | Schubdor HED S 20 300 V4A  | 300 mm | 20 mm | 0.750 kg |
| 550100003857 | Schubdor HED S 20 300 verz | 300 mm | 20 mm | 0.750 kg |
| 550100003860 | Schubdor HED S 22 500 V4A  | 500 mm | 22 mm | 1.500 kg |
| 550100003861 | Schubdor HED S 22 500 verz | 500 mm | 22 mm | 1.500 kg |
| 550100003862 | Schubdor HED S 22 300 V4A  | 300 mm | 22 mm | 0.900 kg |
| 550100003863 | Schubdor HED S 22 300 verz | 300 mm | 22 mm | 0.900 kg |
| 550100003866 | Schubdor HED S 25 500 V4A  | 500 mm | 25 mm | 1.950 kg |
| 550100003867 | Schubdor HED S 25 500 verz | 500 mm | 25 mm | 1.950 kg |
| 550100003868 | Schubdor HED S 25 300 V4A  | 300 mm | 25 mm | 1.150 kg |
| 550100003869 | Schubdor HED S 25 300 verz | 300 mm | 25 mm | 1.150 kg |
| 550100003872 | Schubdor HED S 30 500 V4A  | 500 mm | 30 mm | 2.800 kg |
| 550100003873 | Schubdor HED S 30 500 verz | 500 mm | 30 mm | 2.800 kg |
| 550100003874 | Schubdor HED S 30 350 V4A  | 350 mm | 30 mm | 1.950 kg |
| 550100003875 | Schubdor HED S 30 350 verz | 350 mm | 30 mm | 1.950 kg |

## OPTIONALES ZUBEHÖR

BRM, BRMQ, GK, GS, GSQ

