



JA M20

Hook-head t-bolt


JA M20 have European Technical Assessment ETA-09/0338. They are used to fasten companion structures to W 72/48 and K 72/48 anchor channels and mounting channels. The bolts have hooked heads and a notch at the end of the shaft. They are made of hot-dip galvanised steel or stainless steel. The are available in different lengths. The nuts are included.



Artikel	Typ	L	Festigkeitsklasse	MT	W
JA20150 FV	JORDAHL bolt JA M20x150	150 mm	4.6	M20	0.548 kg
JA20200 FV	JORDAHL bolt JA M20x200	200 mm	4.6	M20	0.652 kg
JA2050 8.8 FV	JORDAHL bolt JA M20x50	50 mm	8.8	M20	0.340 kg
JA2050 FV	JORDAHL bolt JA M20x50	50 mm	4.6	M20	0.340 kg
JA2060 8.8 FV	JORDAHL bolt JA M20x60	60 mm	8.8	M20	0.361 kg
JA2075 8.8 FV	JORDAHL bolt JA M20x75	75 mm	8.8	M20	0.392 kg
JA2075 FV	JORDAHL bolt JA M20x75	75 mm	4.6	M20	0.392 kg
JA20100 8.8 FV	JORDAHL bolt JA M20x100	100 mm	8.8	M20	0.444 kg
JA20100 FV	JORDAHL bolt JA M20x100	100 mm	4.6	M20	0.444 kg
JA20125 8.8 FV	JORDAHL bolt JA M20x125	125 mm	8.8	M20	0.496 kg

DETAIL- UND ANWENDUNGSBILDER





Brandschutz: Ja (1)



Europäische Technische Bewertung: ETA-09/0338

