JAV

JAV Parapet brick anchors are installed at intervals of no more than 750 mm and no more than 375 mm from the edge or corner. This ensures that wind suction and wind pressure loads are absorbed. The parapet brick anchor JAV is made of stainless steel 316 with corrosion resistance class III. It is available in lengths of 600, 850 and 1100 mm and requires 3, 4 or 5 brick tie anchors accordingly.

Article	H	B	L	G
JAV75600 JORDAHL parapet brick anchor 75-600	75 mm	40 mm	600 mm	1.368 kg
JAV75850 JORDAHL parapet brick anchor 75-850	75 mm	40 mm	850 mm	1.901 kg
JAV751100 JORDAHL parapet brick anchor 75-1100	75 mm	40 mm	1100 mm	2.725 kg

H: height
B: width
L: length
G: Weight per storage unit

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Phone: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Issue date: 17.11.2026. Errors and technical changes reserved

DETAIL AND APPLICATION IMAGES

OPTIONAL ACCESSORIES

JMA Series 12

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Phone: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Issue date: 17.11.2026. Errors and technical changes reserved