



JC M10

Hook-head t-bolt

JC M10 have European Technical Assessment ETA-09/0338. They are used to fasten companion structures to W 40+, W 40/22, K 40/22 and K 40/25 anchor channels and mounting channels. The bolts have hooked heads and a notch at the end of the shaft. They are made of hot-dip galvanised steel, galvanised steel or stainless steel. The JC M10 are available in different lengths. The nuts are included.




Artikel	Typ	L	Festigkeitsklasse	MT	W
JC1060 FV	JORDAHL bolt JC M10x60	60 mm	4.6	M10	0.082 kg
JC1030 FV	JORDAHL bolt JC M10x30	30 mm	4.6	M10	0.067 kg
JC1040 FV	JORDAHL bolt JC M10x40	40 mm	4.6	M10	0.072 kg

Artikel	Typ	L	Festigkeitsklasse	MT	W
JC1050 GV	JORDAHL bolt JC M10x50	50 mm	4.6	M10	0.072 kg
JC1060 GV	JORDAHL bolt JC M10x60	60 mm	4.6	M10	0.077 kg
JC1065 GV	JORDAHL bolt JC M10x65	65 mm	4.6	M10	0.079 kg
JC1080 GV	JORDAHL bolt JC M10x80	80 mm	4.6	M10	0.087 kg
JC10100 GV	JORDAHL bolt JC M10x100	100 mm	4.6	M10	0.097 kg
JC1020 GV	JORDAHL bolt JC M10x20	20 mm	4.6	M10	0.057 kg
JC1030 GV	JORDAHL bolt JC M10x30	30 mm	4.6	M10	0.062 kg
JC1040 GV	JORDAHL bolt JC M10x40	40 mm	4.6	M10	0.067 kg

Artikel	Typ	L	MT	W
JC1050 A4	JORDAHL bolt JC M10x50	50 mm	M10	0.073 kg
JC1030 A4	JORDAHL bolt JC M10x30	30 mm	M10	0.063 kg
JC1040 A4	JORDAHL bolt JC M10x40	40 mm	M10	0.068 kg



DETAIL- UND ANWENDUNGSBILDER



Brandschutz: Ja (1)



Europäische Technische Bewertung: ETA-09/0338

