



JD M8

Tee-head bolt

JD M8 have European Technical Assessment ETA-09/0338. They are used to attach companion structures to K 28/28, K 28/15, K 28/12 and W 29/20 anchor channels and mounting channels. They have a hammer-shaped head and a notch at the end of the shaft. The bolts are made of hot-dip galvanised steel, galvanised steel or stainless steel and are available in various lengths. The JD M8 are supplied with the nuts.




Artikel	Typ	L	Festigkeitsklasse	MT	W
JD8100 GV	JORDAHL bolt JD M8x100	100 mm	4.6	M8	0.047 kg
JD815 GV	JORDAHL bolt JD M8x15	15 mm	4.6	M8	0.020 kg
JD8150 GV	JORDAHL bolt JD M8x150	150 mm	4.6	M8	0.063 kg
JD820 GV	JORDAHL bolt JD M8x20	20 mm	4.6	M8	0.021 kg
JD825 GV	JORDAHL bolt JD M8x25	25 mm	4.6	M8	0.023 kg
JD830 GV	JORDAHL bolt JD M8x30	30 mm	4.6	M8	0.024 kg
JD840 GV	JORDAHL bolt JD M8x40	40 mm	4.6	M8	0.028 kg
JD850 GV	JORDAHL bolt JD M8x50	50 mm	4.6	M8	0.031 kg
JD860 GV	JORDAHL bolt JD M8x60	60 mm	4.6	M8	0.034 kg
JD880 GV	JORDAHL bolt JD M8x80	80 mm	4.6	M8	0.040 kg

Artikel	Typ	L	MT	W
JD830 A4	JORDAHL bolt JD M8x30	30 mm	M8	0.025 kg

DETAIL- UND ANWENDUNGSBILDER





Brandschutz: Ja (1)



Europäische Technische Bewertung: ETA-09/0338

