



JGB K 40/25 G

Railing fastening channel for secure fastening of railing posts

The railing fastening channel JGB K 40/25 G has general building authority approval and is made of hot-dip galvanised steel (fv) for indoor use or stainless steel (A4) for outdoor use. The railing fastening channel has a static load-bearing capacity of the normal force (NRd) of 11.1 kN and transverse force (VRd) of 11.1 kN. It is available in lengths of 100 to 250 mm and is paired with the bolts JC M12 - JC M16. The profile is 40 mm wide and 25 mm high. The filling is made of polyethylene (PE).

AbZ

Artikel	Typ	H _p	B _p	L	t	Anzahl der Anker	W
JGBK4025G FVK-0100	JORDAHL railing fastening K40/25	25 mm	40 mm	100 mm	2.75 mm	2 pcs	0.565 kg
JGBK4025G FVK-0120	JORDAHL railing fastening K40/25	25 mm	40 mm	120 mm	2.75 mm	2 pcs	0.611 kg
JGBK4025G FVK-0150	JORDAHL railing fastening K40/25	25 mm	40 mm	150 mm	2.75 mm	2 pcs	0.680 kg
JGBK4025G FVK-0200	JORDAHL railing fastening K40/25	25 mm	40 mm	200 mm	2.75 mm	2 pcs	0.795 kg
JGBK4025G FVK-0220	JORDAHL railing fastening K40/25	25 mm	40 mm	220 mm	2.75 mm	2 pcs	0.841 kg
JGBK4025G FVK-0250	JORDAHL railing fastening K40/25	25 mm	40 mm	250 mm	2.75 mm	2 pcs	1.077 kg

Artikel	Typ	H _p	B _p	L	t	Anzahl der Anker	W
JGBK4025G A4K-0100	JORDAHL railing fastening K40/25	25 mm	40 mm	100 mm	2.75 mm	2 pcs	0.499 kg
JGBK4025G A4K-0120	JORDAHL railing fastening K40/25	25 mm	40 mm	120 mm	2.75 mm	2 pcs	0.538 kg
JGBK4025G A4K-0150	JORDAHL railing fastening K40/25	25 mm	40 mm	150 mm	2.75 mm	2 pcs	0.596 kg
JGBK4025G A4K-0200	JORDAHL railing fastening K40/25	25 mm	40 mm	200 mm	2.75 mm	2 pcs	0.693 kg



PRODUKTINFORMATION

Artikel	Typ	H _p	B _p	L	t	Anzahl der Anker	W
JGBK4025G A4K-0220	JORDAHL railing fastening K40/25	25 mm	40 mm	220 mm	2.75 mm	2 pcs	0.732 kg
JGBK4025G A4K-0250	JORDAHL railing fastening K40/25	25 mm	40 mm	250 mm	2.75 mm	2 pcs	0.943 kg

AbZ

Allgemeine bauaufsichtliche Zulassung: Z-21.4-1913

