


JGB K 50/30 DA

Railing fastening channel for secure fastening of railing posts



The railing fastening channel JGB K 50/30 DA has general building authority approval and is made of hot-dip galvanised steel (fv) for indoor use or stainless steel (A4) for outdoor use. The railing fastening channel has a static load-bearing capacity of the normal force (NRd) of 17.2 kN and transverse force (VRd) of 17.2 kN. It is available in lengths of 100 to 250 mm and is paired with the bolts JB M12 - JB M20. The profile is 50 mm wide and 30 mm high. The filling is made of polyethylene (PE).

AbZ

Artikel	Typ	H _p	B _p	L	t	Anzahl der Anker	W
JGBK5030DA FVK-0100	JORDAHL railing fastening K50/30	30 mm	50 mm	100 mm	3 mm	2 pcs	0.629 kg
JGBK5030DA FVK-0120	JORDAHL railing fastening K50/30	30 mm	50 mm	120 mm	3 mm	2 pcs	0.634 kg
JGBK5030DA FVK-0150	JORDAHL railing fastening K50/30	30 mm	50 mm	150 mm	3 mm	2 pcs	0.722 kg
JGBK5030DA FVK-0200	JORDAHL railing fastening K50/30	30 mm	50 mm	200 mm	3 mm	2 pcs	0.960 kg
JGBK5030DA FVK-0220	JORDAHL railing fastening K50/30	30 mm	50 mm	220 mm	3 mm	2 pcs	1.026 kg
JGBK5030DA FVK-0250	JORDAHL railing fastening K50/30	30 mm	50 mm	250 mm	3 mm	2 pcs	1.274 kg

Artikel	Typ	H _p	B _p	L	t	Anzahl der Anker	W
JGBK5030DA A4K-0100	JORDAHL railing fastening K50/30	30 mm	50 mm	100 mm	3 mm	2 pcs	0.563 kg
JGBK5030DA A4K-0120	JORDAHL railing fastening K50/30	30 mm	50 mm	120 mm	3 mm	2 pcs	0.622 kg
JGBK5030DA A4K-0150	JORDAHL railing fastening K50/30	30 mm	50 mm	150 mm	3 mm	2 pcs	0.710 kg
JGBK5030DA A4K-0200	JORDAHL railing fastening K50/30	30 mm	50 mm	200 mm	3 mm	2 pcs	0.856 kg



PRODUKTINFORMATION

Artikel	Typ	H _p	B _p	L	t	Anzahl der Anker	W
JGBK5030DA A4K-0220	JORDAHL railing fastening K50/30	30 mm	50 mm	220 mm	3 mm	2 pcs	0.915 kg
JGBK5030DA A4K-0250	JORDAHL railing fastening K50/30	30 mm	50 mm	250 mm	3 mm	2 pcs	1.138 kg

AbZ

Allgemeine bauaufsichtliche Zulassung: Z-21.4-1913

