



JLA

The facing masonry must be secured against buckling and also be able to dissipate high wind forces into the load-bearing component. Depending on the material of the load-bearing interior wall, this is performed by JLA cavity wall anchors or brick tie anchors. The JLA dowel anchor is a cavity wall anchor pre-mounted with dowels for the subsequent facing of masonry walls made of solid brick or concrete walls. There is no need to bend it into the facing shell thanks to its corrugated shape. JLA cavity wall anchors are made of stainless steel of corrosion resistance class III as standard.

Artikel	Typ	L	W
LSA 01-4X250	Cavity wall ties typ JLA D-ZV-4/250	250 mm	0.024 kg
LSA 01-4X300	Cavity wall ties typ JLA D-ZV-4/300	300 mm	0.029 kg
LSA 01-4X350	Cavity wall ties typ JLA D-ZV-4/350	350 mm	0.035 kg
LSA 01-4X400	Cavity wall ties type JLA D-ZV-4/400	400 mm	0.040 kg
LSA 01-5X350	Cavity wall ties type JLA D-ZV-5/350	350 mm	0.054 kg
LSA 01-5X400	Cavity wall ties type JLA D-ZV-5/400	400 mm	0.065 kg
LSA 01-5X450	Cavity wall ties type JLA D-ZV-5/450	450 mm	0.073 kg
LSA 01-5X500	Cavity wall ties type JLA D-ZV-5/500	500 mm	0.081 kg
LSA 01-5X550	Cavity wall ties type JLA D-ZV-5/550	550 mm	0.088 kg

OPTIONALES ZUBEHÖR

JVA-TS, KKP

