



JM K 40/25

Mounting channels, cold-formed

The mounting channel JM K 40/25 has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 11.2 kN. The mounting channel is available in the standard length of 6000 mm and is paired with the bolts JC M10 - JC M16. The profile is 40 mm wide and 25 mm high.



Artikel	Typ	H _p	B _p	L	t	A	W
JMK4025 R-6000	JORDAHL mounting channel K40/25	25 mm	40 mm	6000 mm	2.75 mm	2.659 cm ²	12.522 kg

Artikel	Typ	H _p	B _p	L	t	A	W
JMK4025 FV-6000	JORDAHL mounting channel K40/25	25 mm	40 mm	6000 mm	2.75 mm	2.659 cm ²	13.770 kg

Artikel	Typ	H _p	B _p	L	t	A	W
JMK4025 A2-6000	JORDAHL mounting channel K40/25	25 mm	40 mm	6000 mm	2.75 mm	2.659 cm ²	11.502 kg

Artikel	Typ	H _p	B _p	L	t	A	W
JMK4025 A4-6000	JORDAHL mounting channel K40/25	25 mm	40 mm	6000 mm	2.75 mm	2.659 cm ²	11.646 kg



OPTIONALES ZUBEHÖR

JGM C



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE

