



# JM K 50/30

Mounting channels, cold-formed

The mounting channel JM K 50/30 has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 16.8 kN. The mounting channel is available in the standard length of 6000 mm and is paired with the bolts JB M10 - JB M20. The profile is 50 mm wide and 30 mm high.



| Artikel        | Typ                             | H <sub>p</sub> | B <sub>p</sub> | L       | t       | A                     | W         |
|----------------|---------------------------------|----------------|----------------|---------|---------|-----------------------|-----------|
| JMK5030 R-6000 | JORDAHL mounting channel K50/30 | 30 mm          | 50 mm          | 6000 mm | 3.25 mm | 3.839 cm <sup>2</sup> | 18.078 kg |

| Artikel         | Typ                             | H <sub>p</sub> | B <sub>p</sub> | L       | t       | A                     | W         |
|-----------------|---------------------------------|----------------|----------------|---------|---------|-----------------------|-----------|
| JMK5030 FV-6000 | JORDAHL mounting channel K50/30 | 30 mm          | 50 mm          | 6000 mm | 3.25 mm | 3.839 cm <sup>2</sup> | 19.884 kg |

| Artikel         | Typ                             | H <sub>p</sub> | B <sub>p</sub> | L       | t       | A                     | W         |
|-----------------|---------------------------------|----------------|----------------|---------|---------|-----------------------|-----------|
| JMK5030 A4-6000 | JORDAHL mounting channel K50/30 | 30 mm          | 50 mm          | 6000 mm | 3.25 mm | 3.839 cm <sup>2</sup> | 17.592 kg |

## OPTIONALES ZUBEHÖR

JGM B



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE

