



JM W 50/30

Mounting channels, hot-rolled

The mounting channel JM W 50/30 is approved throughout Europe by ETA-15/0386. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) and rolled plain steel (wb). This mounting channel has a static load-bearing capacity of the normal force (NRd) of 20.6 kN and shear force (VRd) of 20.2 kN. It is available with a total length of 6000 mm and is paired with the bolts JB M10 - JB M20. The profile is 50 mm wide and 30 mm high.



Artikel	Typ	H _p	B _p	L	t	A	W
JMW5030 R-6000	JORDAHL mounting channel W50/30	30 mm	50 mm	6000 mm	2.75 mm	4.204 cm ²	20.541 kg

Artikel	Typ	H _p	B _p	L	t	A	W
JMW5030 FV-6000	JORDAHL mounting channel W50/30	30 mm	50 mm	6000 mm	2.75 mm	4.204 cm ²	21.540 kg

Artikel	Typ	H _p	B _p	L	t	A	W
JMW5030 A4-6000	JORDAHL mounting channel W50/30	30 mm	50 mm	6000 mm	2.75 mm	4.204 cm ²	20.202 kg

DETAIL- UND ANWENDUNGSBILDER



OPTIONALES ZUBEHÖR

JGM B





Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE



Europäische Technische Bewertung: ETA-15/0386

