



JML K 28/15

Mounting channels, cold-formed, perforated

The mounting channel JML K 28/15 has environmental product declaration EPD-JDL-20200260-IBB1-DE and is made of hot-dip galvanised steel (fv), stainless steel (A4) or rolled plain steel (wb). It has a static load-bearing capacity of the normal force (NRd) of 4.9 kN. The mounting channel is available in lengths of 100 to 6000 mm and is paired with the bolts JD M6 - JD M12. The profile is 28 mm wide and 15 mm high.



Artikel	Typ	H _p	B _p	L	t	A	W
LSK2815 R-6000	JORDAHL slotted channel K28/15	15 mm	28 mm	6000 mm	2.3 mm	1.21 cm ²	6.120 kg

Artikel	Typ	H _p	B _p	L	t	A	W
LSK2815 FV-6000	JORDAHL slotted channel K28/15	15 mm	28 mm	6000 mm	2.3 mm	1.21 cm ²	6.732 kg

Artikel	Typ	H _p	B _p	L	t	A	W
LSK2815 A4-6000	JORDAHL slotted channel K28/15	15 mm	28 mm	6000 mm	2.3 mm	1.21 cm ²	6.240 kg

OPTIONALES ZUBEHÖR

JGM D, JMA Series 12, JMA-D Series 12, JMA-Q Series 12, JMA-QE Series 12, JNA Series 12, JVB-Z, JVB-ZS



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE

