



JTA K 72/48

Anchor channel, cold-formed, with round or I anchor

The JTA K 72/48 anchor channel is approved throughout Europe by ETA-09/0338. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JA M20 - JA M30. The profile is 72 mm wide and 48 mm high. The filling is made of polyethylene (PE).



Artikel	Typ	H	H _p	B _p	L	t	Anzahl der Anker	W
JTAK7248-0250-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	250 mm	6 mm	2 pcs	2.832 kg
JTAK7248-0350-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	350 mm	6 mm	2 pcs	3.724 kg
JTAK7248-0300-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	300 mm	6 mm	2 pcs	3.278 kg
JTAK7248-0400-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	400 mm	6 mm	3 pcs	4.472 kg
JTAK7248-0550-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	550 mm	6 mm	3 pcs	5.810 kg
JTAK7248-0800-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	800 mm	6 mm	4 pcs	8.341 kg
JTAK7248-1050-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	1050 mm	6 mm	5 pcs	10.872 kg
JTAK7248-6000-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	6000 mm	6 mm	21 pcs	9.974 kg
JTAK7248-0150-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	150 mm	6 mm	2 pcs	1.941 kg
JTAK7248-0200-FVKCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	200 mm	6 mm	2 pcs	2.387 kg



PRODUKTINFORMATION

Artikel	Typ	H	H _p	B _p	L	t	Anzahl der Anker	W
JTAK7248-6000-A4KCE	JORDAHL anchor channel K72/48	195 mm	48 mm	72 mm	6000 mm	6 mm	21 pcs	9.241 kg

OPTIONALES ZUBEHÖR

JGM A



Brandschutz: Ja (1)



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE



Europäische Technische Bewertung: ETA-09/0338

