



JTA RT W 40/22

Anchor channel, hot-rolled, for fastening façades to ceiling tops

The anchor channel JTA RT W 40/22 is made of hot-dip galvanised steel (fv) or stainless steel (A4). The JTA RT W 40/22 has round anchors and reinforcing bars made of reinforcing steel. It is available in profile lengths from 150 to 550 mm and in several variants for the concrete cover and is paired with the bolts JC M10 - JC M16. The filling is made of polyethylene (PE).

Artikel	Typ	H	B	L	W
JTARTW4022-0300-07-FVK	JORDAHL anchor channel RT W40/22 type 07	490 mm	40 mm	300 mm	1.110 kg
JTARTW4022-0350-01-FVK	JORDAHL anchor channel RT W40/22 type 01	34 mm	40 mm	350 mm	1.180 kg
JTARTW4022-0350-02-FVK	JORDAHL anchor channel RT W40/22 type 02	365 mm	40 mm	350 mm	1.200 kg
JTARTW4022-0350-03-FVK	JORDAHL anchor channel RT W40/22 type 03	390 mm	40 mm	350 mm	1.210 kg
JTARTW4022-0350-04-FVK	JORDAHL anchor channel RT W40/22 type 04	415 mm	40 mm	350 mm	1.230 kg
JTARTW4022-0350-05-FVK	JORDAHL anchor channel RT W40/22 type 05	440 mm	40 mm	350 mm	1.250 kg
JTARTW4022-0350-06-FVK	JORDAHL anchor channel RT W40/22 type 06	465 mm	40 mm	350 mm	1.260 kg
JTARTW4022-0350-07-FVK	JORDAHL anchor channel RT W40/22 type 07	490 mm	40 mm	350 mm	1.280 kg

DETAIL- UND ANWENDUNGSBILDER



OPTIONALES ZUBEHÖR

JGM C, JVL

