



JTA W 55/42

Anchor channel, hot-rolled, with round or I anchor

The anchor channel JTA W 55/42 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JB M16 - JB M24. The profile is 55 mm wide and 42 mm high. The filling is made of polyethylene (PE).



Artikel	Typ	H	H _p	B _p	L	t	Anzahl der Anker	W
JTAW5542-0150-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	150 mm	5 mm	2 pcs	1.705 kg
JTAW5542-0200-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	200 mm	5 mm	2 pcs	2.077 kg
JTAW5542-6000-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	6000 mm	5 mm	21 pcs	8.466 kg
JTAW5542-0250-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	250 mm	5 mm	2 pcs	2.448 kg
JTAW5542-0300-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	300 mm	5 mm	2 pcs	2.820 kg
JTAW5542-0350-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	350 mm	5 mm	2 pcs	3.191 kg
JTAW5542-0400-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	400 mm	5 mm	3 pcs	3.859 kg
JTAW5542-0550-FVKCE	JORDAHL anchor channel W55/42	190 mm	42 mm	55 mm	550 mm	5 mm	3 pcs	4.973 kg



Brandschutz: Ja (1)



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE



ETA

Europäische Technische Bewertung: ETA-09/0338

