



JVB-ZS

Connection straps

The toothed connection straps JVB-ZS with welded-on bolts are suitable for transmitting tensile and compressive forces. They are available in various lengths and made of either galvanised steel or stainless steel. The series 12 connection strap JVB-ZS is suitable for profiles of the anchor channels JTA K 28/15. Series 18 is suitable for K 38/17 rail profiles.

Artikel	Typ	H	B	L	L1	L2	W
JVB115ZS12 A4		5 mm	30 mm	125 mm	10 mm	115 mm	0.159 kg
JVB115ZS12 GV		5 mm	30 mm	125 mm	10 mm	115 mm	0.159 kg
JVB140ZS12 A4		5 mm	30 mm	147 mm	10 mm	140 mm	0.188 kg
JVB140ZS12 GV	JORDAHL-toothed strap type JVB-140-ZS/12	5 mm	30 mm	147 mm	10 mm	140 mm	0.188 kg
JVB140ZS18 A4		5 mm	30 mm	147 mm	12 mm	140 mm	0.201 kg
JVB140ZS18 GV		5 mm	30 mm	147 mm	12 mm	140 mm	0.201 kg
JVB165ZS12 A4		5 mm	30 mm	172 mm	10 mm	165 mm	0.217 kg
JVB165ZS12 GV		5 mm	30 mm	172 mm	10 mm	165 mm	0.217 kg
JVB165ZS18 A4		5 mm	30 mm	172 mm	12 mm	165 mm	0.230 kg
JVB165ZS18 GV		5 mm	30 mm	172 mm	12 mm	165 mm	0.230 kg
JVB190ZS12 A4		5 mm	30 mm	197 mm	10 mm	190 mm	0.246 kg
JVB190ZS12 GV	JORDAHL-toothed strap type JVB-190-ZS/12	5 mm	30 mm	197 mm	10 mm	190 mm	0.246 kg
JVB190ZS18 A4		5 mm	30 mm	197 mm	12 mm	190 mm	0.260 kg
JVB190ZS18 GV		5 mm	30 mm	197 mm	12 mm	190 mm	0.260 kg
JVB215ZS12 A4		5 mm	30 mm	122 mm	10 mm	215 mm	0.276 kg
JVB215ZS12 GV		5 mm	30 mm	122 mm	10 mm	215 mm	0.276 kg
JVB215ZS18 A4		5 mm	30 mm	122 mm	12 mm	215 mm	0.289 kg
JVB215ZS18 GV		5 mm	30 mm	122 mm	12 mm	215 mm	0.289 kg

