JXA PC W 53/34

Anchor channel, hot-rolled, toothed, ribbed anchor with large undercut profile

The anchor channel JXA PC W 53/34 is made of hot-dip galvanised steel (fv) or stainless steel (A4). The material is 4 mm thick and it can be supplied in any desired length up to a maximum of 6 m. It is paired with the bolts JXB M16 - JXB M20. The profile is 53 mm wide and 34 mm high. The filling is made of polyethylene (PE).

Fire protection

Steel, hot-dip galvanised

Article	H	H_p	B_p	L	t	G
JXAPCW5334-0150-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	150 mm	4 mm	1.351 kg
JXAPCW5334-0200-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	200 mm	4 mm	1.606 kg
JXAPCW5334-0250-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	250 mm	4 mm	1.862 kg
JXAPCW5334-0300-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	300 mm	4 mm	2.117 kg
JXAPCW5334-0350-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	350 mm	4 mm	2.665 kg
JXAPCW5334-0400-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	400 mm	4 mm	2.920 kg
JXAPCW5334-0550-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	550 mm	4 mm	3.686 kg
JXAPCW5334-0800-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	800 mm	4 mm	5.256 kg
JXAPCW5334-1050-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	1050 mm	4 mm	6.825 kg
JXAPCW5334-3000-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	3000 mm	4 mm	19.125 kg
JXAPCW5334-6000-FVK JORDAHL anchor channel toothed PC W53/34	180 mm	34 mm	53 mm	6000 mm	4 mm	6.326 kg

H: installation height
H_p: profile height
B_p: profile width
L: length
t: Material strength profile
G: Weight per storage unit

PohlCon

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Phone: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Issue date: 13.11.2026. Errors and technical changes reserved

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Phone: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Issue date: 13.11.2026. Errors and technical changes reserved

DETAIL AND APPLICATION IMAGES

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Phone: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Issue date: 13.11.2026. Errors and technical changes reserved