

JXA W 29/20

Anchor channel, hot-rolled, toothed, with round or I anchor



The anchor channel JXA W 29/20 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JXD M12 - JXD M12. The profile is 29 mm wide and 20 mm high. The filling is made of polyethylene (PE).



Artikel	Typ	H	H _p	B _p	L	t	Anzahl der Anker	W
JXARW2920 FVK-0550	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	550 mm	2.5 mm	4 pcs	1.116 kg
JXARW2920 FVK-0150	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	150 mm	2.5 mm	2 pcs	0.345 kg
JXARW2920 FVK-0200	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	200 mm	2.5 mm	2 pcs	0.430 kg
JXARW2920 FVK-0250	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	250 mm	2.5 mm	2 pcs	0.515 kg
JXARW2920 FVK-0300	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	300 mm	2.5 mm	3 pcs	0.645 kg
JXARW2920 FVK-0350	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	350 mm	2.5 mm	3 pcs	0.730 kg
JXARW2920 FVK-0400	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	400 mm	2.5 mm	3 pcs	0.816 kg
JXARW2920 FVK-0800	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	800 mm	2.5 mm	5 pcs	1.587 kg
JXARW2920 FVK-1050	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	1050 mm	2.5 mm	6 pcs	2.057 kg
JXARW2920 FVK-3000	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	3000 mm	2.5 mm	16 pcs	5.828 kg
JXARW2920 FVK-6000	JORDAHL anchor channel toothed W29/20	85 mm	20 mm	29 mm	6000 mm	2.5 mm	31 pcs	1.935 kg





Brandschutz: Ja (1)



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE



Europäische Technische Bewertung: ETA-09/0338

