



JXA W 64/44

Anchor channel, hot-rolled, toothed, with round or I anchor

The anchor channel JXA W 64/44 is approved throughout Europe by ETA-09/0338 and almost worldwide by ICC-ES ESR-2854. It also has environmental product declaration EPD-JDL-20200260-IBB1-DE. It is made of hot-dip galvanised steel (fv) or stainless steel (A4). It can be supplied in any desired length up to a maximum of 6 m and is paired with the bolts JXE M20 - JXE M24. The profile is 64 mm wide and 44 mm high. The filling is made of polyethylene (PE).



Artikel	Typ	H	H _p	B _p	L	t	Anzahl der Anker	W
JXAW6444-0150-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	150 mm	5 mm	2 pcs	1.800 kg
JXAW6444-0200-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	200 mm	5 mm	2 pcs	2.203 kg
JXAW6444-0250-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	250 mm	5 mm	2 pcs	2.607 kg
JXAW6444-0300-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	300 mm	5 mm	2 pcs	3.010 kg
JXAW6444-0350-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	350 mm	5 mm	3 pcs	3.709 kg
JXAW6444-0400-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	400 mm	5 mm	3 pcs	4.112 kg
JXAW6444-6000-FVK	JORDAHL anchor channel toothed W64/44	190 mm	44 mm	64 mm	6000 mm	5 mm	25 pcs	9.296 kg



Brandschutz: Ja (1)



Umweltproduktdeklaration (EPD): EPD-JDL-20200260-IBB1-DE



Europäische Technische Bewertung: ETA-09/0338

