



JXD M12

Toothed t-bolt

JXD M12 have the general Building authority approval Z-21.4-1690. They are used in conjunction with W 29/20 toothed anchor channels and are made of hot-dip galvanised steel or stainless steel. Another feature of the bolts are the two notches at the end of the shaft. The JXD M12 are available in different lengths. The nuts are included.

AbZ


Artikel	Typ	L	W
JXD1240 FA-70	JORDAHL toothed bolt JXD M12x40	40 mm	0.062 kg
JXD1260 FA-70	JORDAHL toothed bolt JXD M12x60	60 mm	0.076 kg
JXD1280 FA-70	JORDAHL toothed bolt JXD M12x80	80 mm	0.091 kg

Artikel	Typ	L	Festigkeitsklasse	W
JXD12100 8.8 FV	JORDAHL toothed bolt JXD M12x100	100 mm	8.8	0.108 kg
JXD12150 8.8 FV	JORDAHL toothed bolt JXD M12x150	150 mm	8.8	0.144 kg
JXD1230 8.8 FV	JORDAHL toothed bolt JXD M12x30	30 mm	8.8	0.057 kg
JXD1240 8.8 FV	JORDAHL toothed bolt JXD M12x40	40 mm	8.8	0.064 kg
JXD1250 8.8 FV	JORDAHL toothed bolt JXD M12x50	50 mm	8.8	0.072 kg
JXD1260 8.8 FV	JORDAHL toothed bolt JXD M12x60	60 mm	8.8	0.079 kg
JXD1280 8.8 FV	JORDAHL toothed bolt JXD M12x80	80 mm	8.8	0.093 kg

Artikel	Typ	L	Festigkeitsklasse	W
JXD12100 8.8 GV	JORDAHL toothed bolt JXD M12x100	100 mm	8.8	0.105 kg
JXD1230 8.8 GV	JORDAHL toothed bolt JXD M12x30	30 mm	8.8	0.054 kg
JXD1250 8.8 GV	JORDAHL toothed bolt JXD M12x50	50 mm	8.8	0.068 kg



DETAIL- UND ANWENDUNGSBILDER



AbZ

Allgemeine bauaufsichtliche Zulassung: Z-21.4-1690

