




KUNEX® Clamp Joint Tape

Clamp joint tape, internal/external, for connecting new buildings to existing buildings

Internal or external KUNEX® PVC-P clamp joint tape is used to form watertight expansion joints in connections between buildings. The joint tapes absorb expansion and shear movements and are available in accordance with DIN and with abP (German building code test certificate). DIN joint tapes are available in bitumen-compatible versions on request. The expansion joint can be up to 30 mm wide and the resulting deformation (vr) max. 20 mm. Clamp joint tapes are usually manufactured as prefabricated joint tape structures specially designed for the particular installation situation.


AbP

Artikel	Typ	H _p	B	Width hollow section	Width expansion element	No. of stop anchors	W
120500002730	Kunex D180 170K DIN	26 mm	180 mm	25 mm	95 mm	0	3.100 kg
120600002762	Kunex DA180 170K DIN	35 mm	180 mm	25 mm	60 mm	3	3.600 kg

Artikel	Typ	H _p	B	Width hollow section	Width expansion element	No. of stop anchors	W
120500002731	Kunex D180 170K DIN BV	26 mm	180 mm	25 mm	95 mm	0	3.200 kg
120600002763	Kunex DA180 170K DIN BV	35 mm	180 mm	25 mm	60 mm	3	3.900 kg
120600002780	Kunex DA320 KB DIN BV	4 mm	320 mm	20 mm	100 mm	0	1.990 kg
120600002782	Kunex DA320 KE DIN BV	20 mm	320 mm	20 mm	100 mm	3	2.300 kg



DETAIL- UND ANWENDUNGSBILDER



OPTIONALES ZUBEHÖR

Primer, Shear Connector, Anchor Rod, Concrete Bolt, Crude Rubber Strips, Clamping Rail, Special Profile, External or Internal Corner, Clamping Protection Profile



General building authority test certificate: P-5316/053/14 MPA-BS

