



PENTAFLEX® ABS V-S Floor/Floor

Sealing formwork element, reinforced

The component PENTAFLEX® ABS V-S Floor/Floor is a formwork element that is used to create waterproof construction joints in the floor-to-floor connection area of reinforced concrete components. The ABS-R version with a reinforced lattice girder construction is suitable for interlocking joint versions according to DIN EN 1992-1-1/NA (EC2). The formwork element is made of DC04 steel and has been verified as watertight up to 5.0 bar. It is 2400 mm long and 600 to 1990 mm high. Other length dimensions, e.g. short or conical pieces, are also available on request.



Artikel	Typ	H	W
112200022099	Penta ABS VS BD 700 790	700-790 mm	5.210 kg
112200022101	Penta ABS VS BD 900 990	900-990 mm	7.150 kg
112200022103	Penta ABS VS BD 1100 1190	1100-1190 mm	9.400 kg
112200022105	Penta ABS VS BD 1300 1390	1300-1390 mm	10.940 kg
112200022107	Penta ABS VS BD 1500 1590	1500-1590 mm	11.820 kg
112200022109	Penta ABS VS BD 1700 1790	1700-1790 mm	14.490 kg
112200022111	Penta ABS VS BD 1900 1990	1900-1990 mm	16.810 kg



Europäische Technische Bewertung: ETA-15/0003

