



# PENTAFLEX® ABS V-S Wall/Wall

Sealing formwork element, reinforced

The component PENTAFLEX® ABS V-S Wall/Wall is a formwork element that is used to create waterproof construction joints in the wall-to-wall connection area of reinforced concrete components. The ABS-R version with a reinforced lattice girder construction is suitable for interlocking joint versions according to DIN EN 1992-1-1/NA (EC2). The formwork element is made of DC04 steel and has been verified as watertight up to 5.0 bar. It is 2400 mm long and 600 to 1990 mm high. Other length dimensions, e.g. short or conical pieces, are also available on request.



| Artikel      | Typ                       | H          | W        |
|--------------|---------------------------|------------|----------|
| 112200022098 | Penta ABS VS BD 600 690   | 600-690 mm | 4.820 kg |
| 112200022100 | Penta ABS VS BD 800 890   | 800-890 mm | 6.780 kg |
| 112200022102 | Penta ABS VS BD 1000 1090 |            |          |
| 112200022104 | Penta ABS VS BD 1200 1290 |            |          |
| 112200022106 | Penta ABS VS BD 1400 1490 |            |          |
| 112200022108 | Penta ABS VS BD 1600 1690 |            |          |
| 112200022110 | Penta ABS VS BD 1800 1890 |            |          |



Europäische Technische Bewertung: ETA-15/0003

