PENTAFLEX® Floor Drain PP

Waterproof penetration

The PENTAFLEX® Floor Drain PP is designed for use with watertight reinforced concrete slabs and consists of a PP pipe and a slotted grate made of stainless steel or ABS plastic. It can be walked on and, depending on the version, can bear loads of up to 0.3 t. The pipe diameter DN is 110 mm. Top section height-adjustable by 50 mm. The floor drain is also available with fire resistance class R 90 or Multistop on request.

Article	Max. load (kg)	Diameter Nominal	Measurements Cover	Material of the cover	G
111200004235 Boden 110 1,5 Edel	1500.0 kg	110 mm	138x138 mm	Stainless steel	1.558 kg
111200004236 Boden 110 0,3 ABS	300.0 kg	110 mm	138x138 mm	ABS	1.176 kg
111200004238 Boden 110 0,3 Edel	300.0 kg	110 mm	138x138 mm	Stainless steel	1.338 kg

G: Weight per storage unit

OPTIONAL ACCESSORIES

PENTAFLEX® Floor Drain Extension

PohlCon

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Phone: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Issue date: 17.11.2026. Errors and technical changes reserved