RAPIDOBAT® Cretcon HD

Formwork tube for pore-free concrete surfaces

RAPIDOBAT® Cretcon HD is a round formwork tube that produces particularly high-quality concrete columns with the help of an activatable hydrogel formlining skin. The concrete surface achieves the highest exposed concrete class SB 4, the highest porosity class P 4 and the highest colour uniformity class FT 3, among other things. The formwork tubes consist of multi-layered paper and cardboard sheets that retain their shape even in driving rain. They have an integrated ripcord for easy stripping of the formwork. We provide this component with inner diameters from 200 to 800 mm and a stock length of up to 7000 mm. Other diameters and lengths are available on request.

Artikel	Typ	H_F	Ø ext	Ø	W
310300001830	RAC 200-m	7000 mm	207 mm	200 mm	2.094 kg
310300001832	RAC 240-m	7000 mm	247 mm	240 mm	2.905 kg
310300001833	RAC 250-m	7000 mm	257 mm	250 mm	3.025 kg
310300001835	RAC 300-m	7000 mm	309 mm	300 mm	3.985 kg
310300001837	RAC 350-m	7000 mm	359 mm	350 mm	5.016 kg
310300001838	RAC 360-m	7000 mm	369 mm	360 mm	5.362 kg
310300001839	RAC 400-m	7000 mm	409 mm	400 mm	6.168 kg
310300001840	RAC 435-m	7000 mm	444 mm	435 mm	6.688 kg
310300001841	RAC 450-m	7000 mm	461 mm	450 mm	7.923 kg
310300001842	RAC 500-m	7000 mm	513 mm	500 mm	9.620 kg
310300001843	RAC 560-m	7000 mm	573 mm	560 mm	10.775 kg
310300001844	RAC 600-m	7000 mm	613 mm	600 mm	11.554 kg
310300001845	RAC 650-m	7000 mm	665 mm	650 mm	13.948 kg
310300001846	RAC 700-m	7000 mm	715 mm	700 mm	15.040 kg
310300001847	RAC 750-m	7000 mm	767 mm	750 mm	17.762 kg
310300001848	RAC 800-m	7000 mm	817 mm	800 mm	20.746 kg
310300013184	RAC 550-m	7000 mm	563 mm	550 mm	10.590 kg

PohlCon

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Ausgabedatum: 22.05.2025. Irrtümer und technische Änderungen vorbehalten

OPTIONALES ZUBEHÖR

Capitals, Bases, Release Agent for Capitals and Bases, RAPIDO-Clamp Type D-Set, RAPIDO-Clamp Type M

PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

Ausgabedatum: 22.05.2025. Irrtümer und technische Änderungen vorbehalten