


SEMS

Hexagonal nut with flange, DIN EN 1661



Hexagon nuts with flange SEMS (in line with DIN EN 1661) are used in combination with suitable bolts in numerous applications, e.g. when installing ceiling brackets, storm protection brackets for cable trays, cable ladders or outlet plates. The nuts are available in threads M6 to M10. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

Artikel	Typ	t	D	Ø	SW	W
SEMS 10	Hexagon nut, self-locking	9.50 mm	21 mm	10 mm	17 mm	0.010 kg
SEMS 6	Hexagon nut, self-locking	5.50 mm	14 mm	6 mm	10 mm	0.002 kg
SEMS 8	Hexagon nut, self-locking	7.50 mm	17 mm	8 mm	13 mm	0.006 kg

Artikel	Typ	t	D	Ø	SW	W
SEMS 10E	hexagon nut, self-locking	9.50 mm	21 mm	10 mm	15 mm	0.011 kg
SEMS 6E	Hexagon nut, self-locking	5.50 mm	14 mm	6 mm	10 mm	0.003 kg
SEMS 8E	Hexagon nut, self-locking	7.50 mm	17 mm	8 mm	13 mm	0.006 kg

DETAIL- UND ANWENDUNGSBILDER



