


SK

Hexagon nut in accordance with DIN EN ISO 4032



Hexagon nuts SK according to DIN EN ISO 4032 are made of stainless steel (A4) or galvanised steel of strength class 8 and are available with various threads from M6 to M30. For alternating loads, we recommend using self-locking nuts.

Artikel	Typ	W
SK10 A4 ISO 4032	Hexagon nut ISO 4032 - M10	0.011 kg
SK10 FV ISO 4032	Hexagon nut ISO 4032 - M10 - 8	0.012 kg
SK10 GV ISO 4032	Hexagon nut ISO 4032 - M10 - 8	0.010 kg
SK12 A4 ISO 4032	Hexagon nut ISO 4032 - M12	0.017 kg
SK12 FV ISO 4032	Hexagon nut ISO 4032 - M12 - 8	0.018 kg
SK12 GV ISO 4032	Hexagon nut ISO 4032 - M12 - 8	0.016 kg
SK16 A4 ISO 4032	Hexagon nut ISO 4032 - M16	0.041 kg
SK16 FV ISO 4032	Hexagon nut, ISO 4032 - M16 - 8	0.044 kg
SK16 GV ISO 4032	Hexagon nut ISO 4032 - M16 - 8	0.040 kg
SK20 A4 ISO 4032	Hexagon nut ISO 4032 - M20	0.077 kg
SK20 FV ISO 4032	Hexagon nut, ISO 4032 - M20 - 8	0.083 kg
SK20 GV ISO 4032	Hexagon nut ISO 4032 - M20 - 8	0.076 kg
SK24 A4 ISO 4032	Hexagon nut ISO 4032 - M24	0.134 kg
SK24 GV ISO 4032	Hexagon nut ISO 4032 - M24 - 8	0.131 kg
SK6 A4 ISO 4032	Hexagon nut ISO 4032 - M6	0.003 kg
SK6 GV ISO 4032	Hexagon nut ISO 4032 - M6 - 8	0.002 kg
SK8 A4 ISO 4032	Hexagon nut ISO 4032 - M8	0.017 kg
SK24 FV ISO 4032	Hexagon nut, ISO 4032 - M12 - 8	0.144 kg
SK8 GV ISO 4032	Hexagon nut ISO 4032 - M8 - 8	0.005 kg



DETAIL- UND ANWENDUNGSBILDER

