


UBDHB350 2R

False floor socket, 2x, round





The UBDHB350 2R components are false floor sockets that are installed as pull boxes and built-in boxes on screed-covered underfloor ducts. They have a mounting hole to accommodate a formwork pipe, which is replaced by a round plastic or stainless steel installation unit during final assembly. The supplied earthing clamps are used for equipotential bonding. The floor sockets with side walls that can be bent open on all sides are made of sendzimir hot-dip galvanised sheet steel in accordance with DIN EN 10346 and have VDE/TÜV approval in accordance with DIN EN 50085.



Artikel	Typ	H	H _{min}	B1	B2	L1	L2	mounting box	E	Geeignet für estrichbündigen geschlossenen Unterflurkanal	Geeignet für estrichüberdeckten Unterflurkanal	W
UBDHB350 28-259R	floor box-hollow space UBDHB350 28-259R,	31 mm	63 mm	410 mm	450 mm	410 mm	450 mm	2	260 mm	Nein (0)	Ja (1)	3.314 kg
UBDHB350 38-259R	floor box-hollow space UBDHB350 38-259R	41 mm	73 mm	410 mm	450 mm	410 mm	450 mm	2	260 mm	Nein (0)	Ja (1)	3.406 kg
UBDHB350 48-259R	floor box-hollow space UBDHB350 48-259R	51 mm	83 mm	410 mm	450 mm	410 mm	450 mm	2	260 mm	Nein (0)	Ja (1)	3.502 kg

DETAIL- UND ANWENDUNGSBILDER





USR, UN

Load requirements according to: DIN EN 50085