


BKBRDR

Floor duct bend cover with radius and turning bolts



The BKBRDR floor duct bend cover is placed on top of the floor duct bend BKBR and protects cables and supply lines from flying sparks and other mechanical influences. It is 100 to 600 mm wide corresponding to the bend. The floor duct bend cover is made of sendzimir hot-dip galvanised steel and is not embossed. With a maximum compartment size of 200 mm, we guarantee a tested load capacity of 5.00 kN according to EN 50085-2-2. They come with pre-assembled turning bolts.



steel, continously hot galvanized/Sendzimir process

Products	B	t	P_{max}		W
BKBRDR 10S	100 mm	2,00 mm	5,00 kN	HORIZONTAL	0,990 kg
BKBRDR 15S	150 mm	2,00 mm	5,00 kN	HORIZONTAL	1,480 kg
BKBRDR 20S	200 mm	2,00 mm	5,00 kN	HORIZONTAL	2,050 kg
BKBRDR 30S	300 mm	2,00 mm	5,00 kN	HORIZONTAL	3,420 kg
BKBRDR 40S	400 mm	2,00 mm	5,00 kN	HORIZONTAL	5,110 kg
BKBRDR 50S	500 mm	2,00 mm	5,00 kN	HORIZONTAL	7,110 kg
BKBRDR 60S	600 mm	2,00 mm	5,00 kN	HORIZONTAL	9,430 kg

B: width

t: material thickness





P_{max} : maximum load

W: Weight per storage unit

DETAIL AND APPLICATION IMAGES



PRODUCT INFORMATION



OPTIONAL ACCESSORIES

DR-BK, BKDU 100, BKDU 110

DIN

Load requirements according to, EN 50085-2-2

