



## BRM

### Fire-protection collar

The fire protection collar BRM is a mineral wool insulation panel with a coating on one side. It is mounted on shear dowel HED-S or HED-P. It has a fire resistance duration of 90 minutes (R90) in accordance with DIN EN 13501-2. The coating foams up in case of fire and completely seals the joint. The fire protection collar is available in versions 20, 30 and 40 mm thick for joints of the corresponding widths. Fire protection collars can be combined to protect larger joint widths. A maximum clearance of 10 mm is permitted in the joint. The fire protection sleeves are designed for dowels of different sizes and can be combined with GK and GS sliding sleeves.

Products		W
550300002477	BRM 20 20	0,037 kg
550300002478	BRM 20 30	0,053 kg
550300002479	BRM 20 40	0,072 kg
550300002480	BRM 22 20	0,037 kg
550300002481	BRM 22 30	0,053 kg
550300002482	BRM 22 40	0,071 kg
550300002486	BRM 25 20	0,037 kg
550300002487	BRM 25 30	0,053 kg
550300002488	BRM 25 40	0,071 kg
550300002492	BRM 30 20	0,036 kg
550300002493	BRM 30 30	0,052 kg
550300002494	BRM 30 40	0,074 kg

**W:** Weight per storage unit

