



## BRMQ

### Fire-protection collar

The fire protection collar BRMQ is a mineral wool insulation panel with a coating on one side. It is mounted on shear dowel HED-S. It has a fire resistance duration of 90 minutes (R90) in accordance with DIN EN 13501-2. The coating foams up in case of fire and completely seals the joint. The fire protection collar is available in versions 20, 30 and 40 mm thick for joints of the corresponding widths. Fire protection collars can be combined to protect larger joint widths. A maximum clearance of 10 mm is permitted in the joint. The fire protection sleeves are designed for different dowel sizes and can be combined with GSQ sliding sleeves.

Products		weight
550300002495	BRMQ 20 20	0,114 kg
550300002496	BRMQ 20 30	0,134 kg
550300002497	BRMQ 20 40	0,154 kg
550300002498	BRMQ 22 20	0,114 kg
550300002499	BRMQ 22 30	0,134 kg
550300002500	BRMQ 22 40	0,154 kg
550300002501	BRMQ 25 20	0,114 kg
550300002502	BRMQ 25 30	0,134 kg
550300002503	BRMQ 25 40	0,154 kg
550300002504	BRMQ 30 20	0,114 kg
550300002505	BRMQ 30 30	0,134 kg
550300002506	BRMQ 30 40	0,154 kg

