



FB Shuttering Strip AS-CV

Square spacer made of fibre-reinforced concrete

The FB Shuttering Strip AS-CV is made of fibre concrete and expanded metal strips: It is used for the geometrically clean execution of joint in combination with PENTAFLEX® and KUNEX® ABS formwork elements as well as unsealed formwork elements. It ensures that the areas between the reinforcing bars crossing the joint are closed. This improves the waterproofing quality of the concrete in the boundary layer and so also the quality of the subsequent second casting section. The FB Shuttering Strip AS-CV reliably reduces the amount of concrete leaking out and minimises the loss of fine particles. It has a reinforcement spacing of 100, 150 or 200 mm and is available in versions for concrete cover from 30 to 50 mm thick. Due to different expanded metal heights of 80 or 120 mm, the shuttering strip can have total heights between 110 and 170 mm.

Products	weight
620400018716	2,810 kg
620400018717	2,853 kg
620400018718	3,170 kg
620400018719	3,640 kg
620400018720	3,276 kg
620400018721	3,640 kg
620400018722	4,170 kg
620400018723	3,753 kg
620400018724	4,170 kg
620400018725	4,970 kg
620400018726	4,473 kg
620400018727	4,970 kg
620400024250	2,810 kg
620400024251	2,853 kg
620400024252	3,170 kg
620400024253	3,640 kg
620400024254	3,276 kg
620400024255	3,640 kg
620400024256	4,170 kg

Page 1



PRODUCT INFORMATION

Products	weight
620400024257	3,753 kg
620400024258	4,170 kg
620400024259	4,970 kg
620400024260	4,473 kg
620400024261	4,970 kg

