



# FB Shuttering Strip AS-CV

Square spacer made of fibre-reinforced concrete

The FB Shuttering Strip AS-CV is made of fibre concrete and expanded metal strips: It is used for the geometrically clean execution of joint in combination with PENTAFLEX® and KUNEX® ABS formwork elements as well as unsealed formwork elements. It ensures that the areas between the reinforcing bars crossing the joint are closed. This improves the waterproofing quality of the concrete in the boundary layer and so also the quality of the subsequent second casting section. The FB Shuttering Strip AS-CV reliably reduces the amount of concrete leaking out and minimises the loss of fine particles. It has a reinforcement spacing of 100, 150 or 200 mm and is available in versions for concrete cover from 30 to 50 mm thick. Due to different expanded metal heights of 80 or 120 mm, the shuttering strip can have total heights between 110 and 170 mm.

Products	Rebar spacing		Expanded metal	W
620400018716	100 mm	30 mm	80 mm	2,810 kg
620400018717	150 mm	30 mm	80 mm	2,853 kg
620400018718	200 mm	30 mm	80 mm	3,170 kg
620400018719	100 mm	35 mm	80 mm	3,640 kg
620400018720	150 mm	35 mm	80 mm	3,276 kg
620400018721	200 mm	35 mm	80 mm	3,640 kg
620400018722	100 mm	40 mm	80 mm	4,170 kg
620400018723	150 mm	40 mm	80 mm	3,753 kg
620400018724	200 mm	40 mm	80 mm	4,170 kg
620400018725	100 mm	50 mm	80 mm	4,970 kg
620400018726	150 mm	50 mm	80 mm	4,473 kg
620400018727	200 mm	50 mm	80 mm	4,970 kg
620400024250	100 mm	30 mm	120 mm	2,810 kg
620400024251	150 mm	30 mm	120 mm	2,853 kg
620400024252	200 mm	30 mm	120 mm	3,170 kg
620400024253	100 mm	35 mm	120 mm	3,640 kg
620400024254	150 mm	35 mm	120 mm	3,276 kg
620400024255	200 mm	35 mm	120 mm	3,640 kg
620400024256	100 mm	40 mm	120 mm	4,170 kg



# PRODUCT INFORMATION

---

Products	Rebar spacing		Expanded metal	W
620400024257	150 mm	40 mm	120 mm	3,753 kg
620400024258	200 mm	40 mm	120 mm	4,170 kg
620400024259	100 mm	50 mm	120 mm	4,970 kg
620400024260	150 mm	50 mm	120 mm	4,473 kg
620400024261	200 mm	50 mm	120 mm	4,970 kg

W: Weight per storage unit



PohlCon GmbH  
Nobelstraße 51 | 12057 Berlin  
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | [contact@pohlcon.com](mailto:contact@pohlcon.com)

