



## FR Spring washer

Spring washers FR, designed according to the former DIN 127, provide the optimum preload for bolted connections. Sizes B 6 to B 12 are available. We provide components in various materials and surface finishes to ensure that various corrosion protection requirements for different areas of application are met.

steel, galvanic zinc plated

Products	∅	D	W
FR B6	6,1 mm	11,8 mm	0,001 kg
FR B8	8,1 mm	14,8 mm	0,001 kg
FR B10	10,2 mm	18,1 mm	0,002 kg
FR B12	12,2 mm	21,1 mm	0,002 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Products	∅	D	W
FR B6E	6,1 mm	11,8 mm	0,001 kg
FR B8E	8,1 mm	14,8 mm	0,001 kg
FR B10E	10,2 mm	18,1 mm	0,002 kg
FR B12E	12,2 mm	21,1 mm	0,002 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	∅	D	W
FR B6E4	6,1 mm	11,8 mm	0,001 kg
FR B8E4	8,1 mm	14,8 mm	0,001 kg
FR B10E4	10,2 mm	18,1 mm	0,002 kg

Page 1



# PRODUCT INFORMATION

---

Products	∅	D	W
FR B12E4	12,2 mm	21,1 mm	0,002 kg

∅: inner diameter  
D: diameter  
W: Weight per storage unit

## DETAIL AND APPLICATION IMAGES

