



HED-P

Shear dowel

Half of the shear dowel HED-P is provided with a plasticised spring element, which makes a sliding sleeve unnecessary. The other half is made of stainless steel or galvanised steel. This combination makes it ideal for subsequent installation after the first construction phase. Drilling is used to insert the side with the plasticised spring element. The other side is cast during the second casting stage. The dowel shifts at right angles to the joint. Shear forces are transmitted vertically and parallel to the joint. The shear dowel HED-P is available in standard lengths of 300 to 500 mm for various diameters. Other lengths and diameters are available on request.

Products		weight
550200003830	Schubdor HED P 20 500 V4A	1,300 kg
550200003831	Schubdor HED P 20 500 verz	1,300 kg
550200003832	Schubdor HED P 20 V4A	0,750 kg
550200003833	Schubdor HED P 20 verz	0,750 kg
550200003836	Schubdor HED P 22 500 V4A	1,550 kg
550200003837	Schubdor HED P 22 500 verz	1,550 kg
550200003838	Schubdor HED P 22 V4A	0,900 kg
550200003839	Schubdor HED P 22 verz	0,900 kg
550200003842	Schubdor HED P 25 500 V4A	2,200 kg
550200003843	Schubdor HED P 25 500 verz	2,200 kg
550200003844	Schubdor HED P 25 V4A	1,300 kg
550200003845	Schubdor HED P 25 verz	1,297 kg
550200003848	Schubdor HED P 30 500 V4A	2,850 kg
550200003849	Schubdor HED P 30 500 verz	2,850 kg
550200003850	Schubdor HED P 30 V4A	1,950 kg
550200003851	Schubdor HED P 30 verz	1,950 kg



OPTIONAL ACCESSORIES

BRM

