



HED-S

Shear dowel

The shear dowel HED-S consists of a hot-dip galvanised or stainless steel dowel and a sleeve. When combined with the GS/GSQ stainless steel sliding sleeve or GK plastic sliding sleeve, the dowel can be shifted at right angles to the joint and transmits shear forces in a longitudinal and/or transverse direction. The shear dowel HED-S is available in standard lengths of 300 to 500 mm for various diameters. For example, it can absorb rated resistances for the load-bearing capacity of steel of up to 17.5 kN in joints up to 40 mm wide. Other lengths and diameters are available on request.

Products		W
550100003856	Schubdor HED S 20 300 V4A	0,750 kg
550100003857	Schubdor HED S 20 300 verz	0,750 kg
550100003854	Schubdor HED S 20 500 V4A	1,250 kg
550100003855	Schubdor HED S 20 500 verz	1,250 kg
550100003862	Schubdor HED S 22 300 V4A	0,900 kg
550100003863	Schubdor HED S 22 300 verz	0,900 kg
550100003860	Schubdor HED S 22 500 V4A	1,500 kg
550100003861	Schubdor HED S 22 500 verz	1,500 kg
550100003868	Schubdor HED S 25 300 V4A	1,150 kg
550100003869	Schubdor HED S 25 300 verz	1,150 kg
550100003866	Schubdor HED S 25 500 V4A	1,950 kg
550100003867	Schubdor HED S 25 500 verz	1,950 kg
550100003874	Schubdor HED S 30 350 V4A	1,950 kg
550100003875	Schubdor HED S 30 350 verz	1,950 kg
550100003872	Schubdor HED S 30 500 V4A	2,800 kg
550100003873	Schubdor HED S 30 500 verz	2,800 kg

W: Weight per storage unit



OPTIONAL ACCESSORIES

BRM, BRMQ, GK, GS, GSQ

