



JB M10

Hook-head t-bolt

JB M10 have European Technical Assessment ETA-09/0338. They are used to fasten companion structures to W 55/42, W 53/34, K 53/34, W 50+, K 50/40, W 50/30, K 50/30 and K 48/26 anchor channels and mounting channels. The bolts have hooked heads and a notch at the end of the shaft. They are made of hot-dip galvanised steel, galvanised steel or stainless steel. The JB M10 are available in different lengths. The nuts are included.



steel, galvanic zinc plated

Products	L		weight
JB1030 GV	30 mm	4,6	0,078 kg
JB1040 GV	40 mm	4,6	0,083 kg
JB1050 GV	50 mm	4,6	0,088 kg
JB1060 GV	60 mm	4,6	0,093 kg
JB1080 GV	80 mm	4,6	0,103 kg
JB10100 GV	100 mm	4,6	0,113 kg

steel, batch/hot-dip galvanized

Products	L		weight
JB1080 FV	80 mm	4,6	0,110 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L		weight
JB1030 A4	30 mm		0,080 kg
JB1080 A4	80 mm		0,105 kg



L: length

ETA

, ETA-09/0338

