



## JBRM

### Fire-protection collar

The fire protection collar JBRM is a mineral wool insulation board with a coating on one side and is mounted on the JDSD double shear connector. As a system solution, it meets high fire protection requirements and has a fire resistance of 120 minutes (R120) in accordance with DIN EN 13501-2. The coating foams up in case of fire and completely seals the joint. The fire protection collar is available in versions 20 and 30 mm thick for the corresponding joint widths. Fire protection collars can be combined to protect larger joint widths. A maximum clearance of 10 mm is permitted in the joint. The fire protection collars are designed for different mandrel sizes.



Products	H	B	L	weight
BRM2530-30	150 mm	110 mm	30 mm	0,123 kg
BRM400-20	295 mm	150 mm	20 mm	0,259 kg
BRM45-20	165 mm	110 mm	20 mm	0,106 kg
BRM45-30	165 mm	110 mm	30 mm	0,136 kg
BRM450-20	325 mm	150 mm	20 mm	0,286 kg
BRM60-20	180 mm	110 mm	20 mm	0,116 kg
BRM60-30	180 mm	110 mm	30 mm	0,148 kg
BRM90-20	195 mm	110 mm	20 mm	0,125 kg
BRM90-30	195 mm	110 mm	30 mm	0,160 kg
BRM120-20	210 mm	110 mm	20 mm	0,135 kg
BRM120-30	210 mm	110 mm	30 mm	0,173 kg
BRM130-20	220 mm	120 mm	20 mm	0,154 kg
BRM130-30	220 mm	120 mm	30 mm	0,198 kg
BRM150-20	245 mm	130 mm	20 mm	0,186 kg
BRM150-30	245 mm	130 mm	30 mm	0,238 kg
BRM2530-20	150 mm	110 mm	20 mm	0,096 kg

**H:** height  
**B:** width  
**L:** length

Page 1



