


JC M10

Hook-head t-bolt



JC M10 have European Technical Assessment ETA-09/0338. They are used to fasten companion structures to W 40+, W 40/22, K 40/22 and K 40/25 anchor channels and mounting channels. The bolts have hooked heads and a notch at the end of the shaft. They are made of hot-dip galvanized steel, galvanized steel or stainless steel. The JC M10 are available in different lengths. The nuts are included.



steel, galvanic zinc plated

Products	L	W	
JC1020 GV	20 mm	4,6	0,057 kg
JC1030 GV	30 mm	4,6	0,062 kg
JC1040 GV	40 mm	4,6	0,067 kg
JC1050 GV	50 mm	4,6	0,072 kg
JC1060 GV	60 mm	4,6	0,077 kg
JC1065 GV	65 mm	4,6	0,079 kg
JC1080 GV	80 mm	4,6	0,087 kg
JC10100 GV	100 mm	4,6	0,097 kg

steel, batch/hot-dip galvanized

Products	L	W	
JC1030 FV	30 mm	4,6	0,067 kg
JC1040 FV	40 mm	4,6	0,072 kg
JC1060 FV	60 mm	4,6	0,082 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11



PRODUCT INFORMATION

Products	L	W
JC1030 A4	30 mm	0,063 kg
JC1040 A4	40 mm	0,068 kg
JC1050 A4	50 mm	0,073 kg

L: length

W: Weight per storage unit



, ETA-09/0338

