


JC M12

Hook-head t-bolt



JC M12 have European Technical Assessment ETA-09/0338. They are used to fasten companion structures to W 40+, W 40/22, K 40/22 and K 40/25 anchor channels and mounting channels. The bolts have hooked heads and a notch at the end of the shaft. They are made of hot-dip galvanised steel, galvanised steel or stainless steel. The JC M12 are available in different lengths. The nuts are included.



stainless steel, UNS S31803

Products	L	W
JC1240 FA-70	40 mm	0,082 kg
JC1260 FA-70	60 mm	0,090 kg

steel, galvanic zinc plated

Products	L	W
JC1220 GV	20 mm	4,6 0,067 kg
JC1230 8.8 GV	30 mm	8,8 0,074 kg
JC1230 GV	30 mm	4,6 0,074 kg
JC1240 8.8 GV	40 mm	8,8 0,081 kg
JC1240 GV	40 mm	4,6 0,081 kg
JC1250 8.8 GV	50 mm	8,8 0,089 kg
JC1250 GV	50 mm	4,6 0,089 kg
JC1260 8.8 GV	60 mm	8,8 0,096 kg
JC1260 GV	60 mm	4,6 0,096 kg
JC1280 GV	80 mm	4,6 0,110 kg
JC12100 GV	100 mm	4,6 0,125 kg
JC12125 GV	125 mm	4,6 0,143 kg
JC12150 GV	150 mm	4,6 0,161 kg

Page 1



PRODUCT INFORMATION

steel, batch/hot-dip galvanized

Products	L		W
JC1240 8.8 FV	40 mm	8,8	0,087 kg
JC1240 FV	40 mm	4,6	0,087 kg
JC1250 8.8 FV	50 mm	8,8	0,094 kg
JC1250 FV	50 mm	4,6	0,094 kg
JC1260 8.8 FV	60 mm	8,8	0,101 kg
JC1260 FV	60 mm	4,6	0,101 kg
JC1280 8.8 FV	80 mm	8,8	0,116 kg
JC1280 FV	80 mm	4,6	0,116 kg
JC12100 8.8 FV	100 mm	8,8	0,130 kg
JC12100 FV	100 mm	4,6	0,130 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L		W
JC1230 A4	30 mm		0,075 kg
JC1240 A4	40 mm		0,082 kg
JC1250 A4	50 mm		0,090 kg
JC1260 A4	60 mm		0,097 kg
JC1280 A4	80 mm		0,111 kg
JC12100 A4	100 mm		0,126 kg

L: length

W: Weight per storage unit



, ETA-09/0338



Page 2



PohlCon GmbH
Nobelstraße 51 | 12057 Berlin
Telefon: +49 30 68283-04 | Fax: +49 30 68283-383 | contact@pohlcon.com

