



JDA-FT-KL 14

Punching shear reinforcement for transmitting high shear forces in precast slabs

JDA-FT-KL 14 punching shear reinforcements are approved for static and dynamic effects throughout Europe by ETA-13/0136 and have environmental product declaration EPD-JDL-20200260-IBB1-DE. The double-headed anchors are available made from ribbed reinforcing steel. The strip is made of structural steel and the pre-assembled clip on the anchor element is made of plastic. Special solutions are available on request.



Products	H	B	L	weight	
JDA-FT-KL14185240-0002	189 mm	42 mm	240 mm	2 Stk	0,841 kg
JDA-FT-KL14185260-0002	189 mm	42 mm	260 mm	2 Stk	0,854 kg
JDA-FT-KL14185280-0002	189 mm	42 mm	280 mm	2 Stk	0,868 kg
JDA-FT-KL14285400-0002	289 mm	42 mm	400 mm	2 Stk	1,194 kg

Products	H	B	L	weight	
JDA-FT-KL14185360-0003	189 mm	42 mm	360 mm	3 Stk	1,260 kg
JDA-FT-KL14185390-0003	189 mm	42 mm	390 mm	3 Stk	1,281 kg
JDA-FT-KL14185420-0003	189 mm	42 mm	420 mm	3 Stk	1,302 kg

Products	H	B	L	weight	
JDA-FT-KL141851260-0009	189 mm	42 mm	1260 mm	9 Stk	3,906 kg



PRODUCT INFORMATION

Products	H	B	L		weight
JDA-FT-KL141851400-0010	189 mm	42 mm	1400 mm	10 Stk	4,340 kg

Products	H	B	L		weight
JDA-FT-KL141851440-0012	189 mm	42 mm	1440 mm	12 Stk	5,039 kg

H: height
B: width
L: length



, ETA-13/0136



, EPD-JDL-20200260-IBB1-DE

