


JGB K 40/25 DA

Railing fastening channel for secure fastening of railing posts



The railing fastening channel JGB K 40/25 DA has general building authority approval and is made of hot-dip galvanised steel (fv) for indoor use or stainless steel (A4) for outdoor use. The railing fastening channel has a static load-bearing capacity of the normal force (NRd) of 11.1 kN and transverse force (VRd) of 11.1 kN. It is available in lengths of 100 to 250 mm and is paired with the bolts JC M12 - JC M16. The profile is 40 mm wide and 25 mm high. The filling is made of polyethylene (PE).

AbZ

steel, batch/hot-dip galvanized

Products	L	H _p	B _p	W	
JGBK4025DA FVK-0100	100 mm	25 mm	40 mm	2 Stk	0,402 kg
JGBK4025DA FVK-0120	120 mm	25 mm	40 mm	2 Stk	0,448 kg
JGBK4025DA FVK-0150	150 mm	25 mm	40 mm	2 Stk	0,517 kg
JGBK4025DA FVK-0200	200 mm	25 mm	40 mm	2 Stk	0,632 kg
JGBK4025DA FVK-0220	220 mm	25 mm	40 mm	2 Stk	0,678 kg
JGBK4025DA FVK-0250	250 mm	25 mm	40 mm	2 Stk	0,833 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p	W	
JGBK4025DA A4K-0100	100 mm	25 mm	40 mm	2 Stk	0,351 kg
JGBK4025DA A4K-0120	120 mm	25 mm	40 mm	2 Stk	0,499 kg
JGBK4025DA A4K-0150	150 mm	25 mm	40 mm	2 Stk	1,703 kg
JGBK4025DA A4K-0200	200 mm	25 mm	40 mm	2 Stk	0,563 kg
JGBK4025DA A4K-0220	220 mm	25 mm	40 mm	2 Stk	0,629 kg
JGBK4025DA A4K-0250	250 mm	25 mm	40 mm	2 Stk	0,634 kg

L: length
H_p: profile height

Page 1



PRODUCT INFORMATION

B_p: profile width

W: Weight per storage unit

AbZ

