


JGB K 40/25 G

Railing fastening channel for secure fastening of railing posts



The railing fastening channel JGB K 40/25 G has general building authority approval and is made of hot-dip galvanised steel (fv) for indoor use or stainless steel (A4) for outdoor use. The railing fastening channel has a static load-bearing capacity of the normal force (NRd) of 11.1 kN and transverse force (VRd) of 11.1 kN. It is available in lengths of 100 to 250 mm and is paired with the bolts JC M12 - JC M16. The profile is 40 mm wide and 25 mm high. The filling is made of polyethylene (PE).

AbZ

steel, batch/hot-dip galvanized

Products	L	H _p	B _p		weight
JGBK4025G FVK-0100	100 mm	25 mm	40 mm	2 Stk	0,565 kg
JGBK4025G FVK-0120	120 mm	25 mm	40 mm	2 Stk	0,611 kg
JGBK4025G FVK-0150	150 mm	25 mm	40 mm	2 Stk	0,680 kg
JGBK4025G FVK-0200	200 mm	25 mm	40 mm	2 Stk	0,795 kg
JGBK4025G FVK-0220	220 mm	25 mm	40 mm	2 Stk	0,841 kg
JGBK4025G FVK-0250	250 mm	25 mm	40 mm	2 Stk	1,077 kg

Stainless steel, according to ASTM 316 Ti / AISI 316 L, BS 320S17 / BS 316S11

Products	L	H _p	B _p		weight
JGBK4025G A4K-0100	100 mm	25 mm	40 mm	2 Stk	0,499 kg
JGBK4025G A4K-0120	120 mm	25 mm	40 mm	2 Stk	0,538 kg
JGBK4025G A4K-0150	150 mm	25 mm	40 mm	2 Stk	0,596 kg
JGBK4025G A4K-0200	200 mm	25 mm	40 mm	2 Stk	0,693 kg
JGBK4025G A4K-0220	220 mm	25 mm	40 mm	2 Stk	0,732 kg
JGBK4025G A4K-0250	250 mm	25 mm	40 mm	2 Stk	0,943 kg

L: length
H_p: profile height

Page 1



B_p: profile width

AbZ

